




MAMO ENGINEERING



Cable Glands / Halogen Free / NPT






SPRINT cable glands, NSKV, NPT



NSKV



Protection class IP68 (5 bar 30 min) / IP69
Glow wire test 750 °C
Temperature range -40 °C - 100 °C
Material Gland Polyamide, Gasket EPDM

Type	WISKA-No. RAL 7035 LG	WISKA-No. RAL 9005 BK	 D (mm)	 L (mm)	 (mm)	 SW (mm)	TL (mm)	
NSKV 1/4	10062655	10061854	NPT 1/4"	15	3 - 7	16	33 - 38	50
NSKV 3/8	10062656	10061867	NPT 3/8"	15	4,5 - 10	20	35 - 41	50
NSKV 1/2	10062657	10061906	NPT 1/2"	15	6 - 13	24	42 - 51	50
NSKV 3/4	10062658	10061918	NPT 3/4"	15	9 - 17	29	44 - 53	50
NSKV 1	10062659	10061041	NPT 1"	15	13 - 21	36	50 - 59	25
NSKV 1 1/4	10062731	10061492	NPT 1 1/4"	18	16 - 28	46	60 - 73	10
NSKV 1 1/2	10062732	10061501	NPT 1 1/2"	18	21 - 35	55	65 - 78	4
NSKV 2	10062736	10061511	NPT 2"	18	34 - 48	68	69 - 83	3